

SIGN SPECIFICATIONS

1. GENERAL SIGN REQUIREMENTS:

SIGN CODES AND SPECIFICATIONS:

SIGNS SHALL CONFORM TO THE CODES AND SPECIFICATIONS OF THE MOST CURRENT CALIFORNIA MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES (CALIFORNIA MUTCD) UNLESS OTHERWISE NOTED.

2. DETAILED CITY SIGN REQUIREMENTS:

A. RETROREFLECTIVITY

ALL SIGNS CONFORM TO MEET OR EXCEED THE MINIMUM SIGN GRADE AND RETROREFLECTIVITY LEVELS IN PART 1- SIGN, OF CALIFORNIA MUTCD.

B. IDENTIFICATION

IDENTIFICATION SHALL BE PERMANENTLY MARKED ON THE BACK OF ALL SIGNS IN SUCH A POSITION SO AS NOT TO FALL BEHIND ANY POST OR FRAME MEMBER. IDENTIFICATION SHALL INCLUDE THE MANUFACTURER'S NAME, YEAR OF MANUFACTURE, AND RETRO REFLECTIVE GRADE.

C. GUARANTEE

THE COMPLETE SIGN SHALL BE GUARANTEED TO HAVE AN EFFECTIVE PERFORMANCE LIFE OF 10 YEARS MINIMUM AND SHALL BE REPLACED AT NO COST TO THE CITY IF ANY VISIBLE SIGN FAILURE OCCURS WITHIN THAT PERIOD.

D. MOUNTING

ALL SIGNS SHALL BE MOUNTED WITH CITY APPROVED THEFT PROOF MOUNTING.

E. SIGN POSTS

ALL SIGN POSTS IN CONCRETE WALKWAYS/SIDEWALKS OR DIRT EXCEPT ASSEMBLIES SHALL USE 2" X 2" TELESAR SQUARE TUBE 14 U.S.S GAUGE GALVANIZED STEEL SET 18" IN STRUCTURAL GRADE CONCRETE FOUNDATION IN 6" X 6" X 21" HOLE. THE PERFORATED HOLES SHALL BE $\frac{7}{16}$ " IN DIAMETER. ANCHORS SHALL BE 2 $\frac{1}{2}$ " SQUARE HEAVY DUTY ANCHOR 7 U.S.S GAUGE 18" LONG. 1" - 1 $\frac{1}{2}$ " OF THE ANCHOR SHALL REMAIN VISIBLE ABOVE GROUND FOR BREAK-AWAY PURPOSES.

				APPROVED: 	 DATE
CHANGE	DESCRIPTION	DATE	INITIAL	CITY ENGINEER	