



DETAIL  
NOT TO SCALE

SPEED LIMIT	DIMENSION (INCHES)							
	A	B	C	D	E	F	G	H
25 MPH OR LESS	VAR	6	-	1	$\frac{1}{2}$	4	3	$2\frac{1}{4}$
30 TO 40 MPH	VAR	9	$\frac{3}{8}$	$1\frac{1}{2}$	1	6	$4\frac{1}{2}$	$3\frac{3}{8}$
45 MPH AND ABOVE	VAR	12	$\frac{1}{2}$	2	$1\frac{3}{4}$	8	6	4

RECOMMENDED MINIMUM LETTER HEIGHTS ON STREET NAME SIGNS

TYPE OF MOUNTING	TYPE OF STREET OR HIGHWAY	SPEED LIMIT	RECOMMENDED MINIMUM LETTER HEIGHT	
			INITIAL UPPER-CASE	LOWER-CASE
OVERHEAD	ALL TYPES	ALL SPEED LIMITS	12 INCHES	9 INCHES
POST-MOUNTED	MULTI-LANE	MORE THAN 40 MPH	8 INCHES	6 INCHES
POST-MOUNTED	MULTI-LANE	40 MPH OR LESS	6 INCHES	$4\frac{1}{2}$ INCHES
POST-MOUNTED	2-LANE	ALL SPEED LIMITS	6 INCHES*	$4\frac{1}{2}$ INCHES*

\* ON LOCAL TWO-LANE STREETS WITH SPEED OF 25 MPH OR LESS, 4-INCH INITIAL UPPER-CASE LETTERS WITH 3-INCH LOWER-CASE LETTERS MAY BE USED.

SPECIFICATIONS

- GENERAL:** ALL SIGNS TO CONFORM TO SECTION 2D.43 AND 2D.44 OF THE CA-MUTCD. ALL SIGNS ARE TO HAVE RETROREFLECTIVE SURFACES. LETTERING SHALL BE BLOCK LETTERING WITH CAPITAL AND LOWER CASE LETTERING. SPEEDS NOTED ABOVE ARE PRIMA FACIE OR POSTED SPEED LIMITS.
- COLORS:** BORDER AND MESSAGE SHALL BE WHITE (RETROREFLECTIVE) AND BACKGROUND SHALL BE GREEN (RETROREFLECTIVE).
- POSTS:** USE 2" 2" TELESPAR SQUARE TUBE SIGN POST WITH SQUARE HEAVY DUTY 7 U.S.S.  $2\frac{1}{2}$ " GAUGE ANCHOR AND SET IN CONCRETE FOUNDATION 6" X 6" 21". 1" -  $1\frac{1}{2}$ " OF ANCHOR SHALL REMAIN VISIBLE ABOVE GROUND FOR BREAK-AWAY PURPOSES.

CHANGE	DESCRIPTION	DATE	INITIAL	APPROVED:	DATE: 5/24/18
				CITY ENGINEER	